OPERATIONS MANUAL

Video Otoscope

Otoscope Probe, High-Res Camera, LED, Battery Operated or External Light Source





V.O. Manual • Rev. 4 • Effective 5/06

MedRx sells seven different Video Otoscope Configurations with either the Battery Powered Light Source, the LED Light Source or the External Light Source.

We've combined the wiring instructions, trouble shooting & warranty information into one manual.

In addition to the camera, probe and light source each configurations comes with additional components listed below. See the manuals that come with your particular configurations for additional information.

Deluxe Video Otoscope

Printer, Cart & 13" Monitor.

Ultra Lite Video Otoscope Comes with either a flat screen or conventional monitor.

Digital Video Otoscope

Computer, Monitor, Trackball, Footswitch and the MedRx VO Software.

Video Companion

USB2 video capture cable and the MedRx VO Software.

The AVANT™

HIT Box, Speakers, Headsets, Bone & Air Conductors, Mics, Handswitch and Testing, Fitting & Presentation Software.

The AVANT[™] Audiometer

Speakers, Headsets, Bone & Air Conductors, Mics, Handswitch

The AVANT[™] Mobile Office

(AVANT[™] REM Speech & AVANT[™] A²D Audiometer)

Speakers, Headsets, Bone & Air Conductors, Mics, Handswitch

If you would like to upgrade your system call MedRx toll free at 888-392-1234

Contents

| Using The Video | o Otoscope | 4 | | |
|---------------------------------------------------------|-----------------------------------------------------------------|------------------|--|--|
| Battery Operated Light Source - Charging Batteries 5 | | | | |
| Battery Replace | ement WARNING | 6 | | |
| Delu Ultra Digit Video AVAN AVAN & A2 | ms - Battery Operated Light Source: xe Video Otoscope System | 7 7 7 7 | | |
| Wiring Diagrams - LED Light Source: | | | | |
| Delu | xe Video Otoscope System9-10 | 0 | | |
| Ultra | Lite Video Otoscope System9-1 | 0 | | |
| Digit | al Video Otoscope System9-10 | 0 | | |
| | o Companion9-10 | | | |
| | NT™ Audiometer9-10 | | | |
| The | AVANT™1 | 1 | | |
| | m - External Light Source | | | |
| | xe Video Otoscope System12-1 | | | |
| | Lite Video Otoscope System | | | |
| - | al Video Otoscope System12-1 | | | |
| | o Companion12-1 | | | |
| | NT™ Audiometer12-1 | | | |
| | AVANT™10 | | | |
| Trouble Shooting Guide 14 | | | | |
| Cleaning & Disinfecting 15 | | | | |
| Transporting Your Video Otoscope 15 | | | | |
| Limited Warranty 16 | | | | |
| | | | | |



www.medrx-usa.com

1200 Starkey Rd., #105, Largo FL 33771 Toll Free: (888) 392-1234 • (727) 584-9600 Fax: (727) 584-9602 • Email: medrx@medrx-usa.com

Using the Video Otoscope

CAUTION: The MedRx Video Otoscope is only to be used by a person qualified in the use of an Otoscope. Misuse can cause a patient pain and possible injury.

Video otoscopy has multiple purposes in hearing assessment and hearing instrument fitting.

The Video Otoscope is used for:

- · Performing the initial otoscopic examination prior to testing
- Probe microphone placement for Live Speech Mapping measurements
- · Capturing and storing images to the NOAH patient database
- Troubleshooting problems with the hearing aid, such as blocked receivers and microphones.

Always perform an otoscopic examination of the ear canal prior to testing to determine if earwax or other foreign matter will interfere with probe tube insertion. If this is a problem, the patient should be referred to an appropriate resource for removal of the wax or debris. If abnormal ear conditions are noticed on this examination, an appropriate medical referral is recommended before the hearing instrument is fitted.

The speculum cover is always to be used with the system. The speculum cover must be cleaned or replaced between usage per accepted medical practice procedures.


Prior to insertion, the probe should be held within 1/4" of a known object, such as your finger, to check the quality of the image. Sometimes the lens is smeared with cerumen or other matter and will need to be vigorously cleaned with an alcohol wipe in order to provide a clear image.

IMPORTANT: Since the Video Otoscope incorporates glass lenses for image transmission it is breakable. Although the tip is tapered to improve durability, any impact or crushing to the tip may cause serious damage to the instrument.

Battery Operated Light Source

Install Freshly Charged Batteries Every Day

A Second Set Of 3 Batteries Is Supplied So That A Fully Re-Charged Set Is Always Available




Battery Replacement WARNING


IMPORTANT

Grasp the Upper Portion of the Silver Handle, NOT the Probe or Camera, When Unscrewing the Lower Section to Replace the Batteries.

Otherwise, Possible Damage May Occur to the Probe.

Refer to Pictures Below.





Wiring Diagram - Battery Operated Light Source

Deluxe Video Otoscope System

Ultra Lite Video Otoscope System
 Digital Video Otoscope System
 Video Companion System
 AVANT™ Audiometer

• AVANT[™] Mobile Office (AVANT REM Speech & A²D Audiometer)




Wiring Diagram - Battery Operated Light Source





Wiring Diagram - LED Light Source


- Deluxe Video Otoscope System
- Ultra Lite Video Otoscope System
 - Digital Video Otoscope System
- Video Companion System
 AVANT[™] Audiometer




Wiring Diagram Cont. - LED Light Source









Wiring Diagram - LED Light Source




Wiring Diagram - External Light Source



Wiring Diagram Cont. - External Light Source







Trouble Shooting Guide

External Light Source

| Problem | Main Cause | Solution |
|--------------------------------------------------|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Fuzzy or out of focus picture. | Dirty probe tip (dried cerumen) | Vigorously clean probe tip with an alcohol wipe |
| | Short in twin lead cable. | Replace twin lead cable |
| No picture on display | Light Source not turned on | Turn light source on |
| | Loose wire connection | Re-check wire connection |
| Indicator light switch on light source not on | Power supply not plugged in Short in twin lead cable | Plug in power supply Unplug twin cable from light source; see if light comes on, if so replace twin leads cable |
| No light from probe tip | Light source not on Bulb burnt out | Turn on light source Replace bulb |
| Picture is dark | Switch on back of camera in wrong position | Move camera shutter switch to off position |
| | Light source too low | Turn up intensity of light source |
| Cleaning probe does not improve picture | Probe dropped and physically damaged | Call MedRx for service |

This guide was designed to assist you in diagnosing minor problems. Should service be needed, please call MedRx at 888-392-1234 for Technical Support Monday—Friday, EST 9AM to 5PM

Cleaning & Disinfecting

Your MedRx Video OtoScope has been designed to provide years of trouble-free service. Do not remove or open the cabinets of the equipment, as there are no user serviceable components inside.

Cleaning

To keep your system looking new, wipe the exterior of the components with a soft cloth. Stubborn stains may be removed using a cloth moistened with water and mild detergent. Do not allow debris or fluid to enter in the components. Use an alcohol wipe to clean the lens on the end of the Otoscope probe, or a common disinfectant.

Video Otoscope Disinfecting

The Video Otoscope is sealed so that it may be wiped with the following surface cleaners to disinfect: 75% Alcohol • Chlorhexiderm • Cidex • Nolvasan • Parvocide • Parvosol • Roccal • Synphenol

The scope should **NEVER** be heat sterilized, gas sterilized or soaked in liquid because damage may result.

Transportation & Storage

The probe tip cover should be retained and used for additional transportation protection of the videoscope optics while in or out of the foam case.

When transporting or storing your Video Otoscope, it is best to use the original packing case or similar packaging. Store the system in a cool, dry location and do not place your system in direct sunlight. Care must be taken to protect the system from shock, moisture damage and mishandling. Do not place heavy objects on any of the system's components.

To assure proper operation and warranty protection, use manufacturer's replacement components only.

Limited Warranty

MedRx, Inc. warrants the MedRx Video Otoscope System to be free from defects in material and workmanship for one year from the time of purchase. If this system fails to perform as specified during this period, the purchaser is responsible for calling MedRx at 888 392-1234. The company's representative will advise the owner to either return specific components or the entire system to:

MedRx, Inc. 1200 Starkey Road #105 Largo, FL 33771

MedRx will repair or replace any defective parts, fully test and calibrate the system and/or components and ship the system promptly back to the owner. There is no cost for this warranty service, provided the system is one year old or less and has not been misused, abused, or damaged. Such damage includes, but is not limited to, dropping, exposure to excessive heat (greater than 100 degrees F), and water/liquid damage. Repair or replacement of the system as provided under this warranty is the sole and exclusive remedy of the purchaser. MedRx shall not be liable for any consequential or incidental damages, or for breach of any express or implied warranty. Except to the extent of applicable law, any implied warranty, merchantability or fitness of this product is limited to the duration of this warranty.

MedRx will, at its discretion, service and repair out of warranty components at the purchaser's request, charging for parts and labor as necessary.

Components Registration for Customer Information

| Probe Serial Number: |
|-----------------------------------------|
| Camera Serial Number: |
| Super Nova™ Light Source Serial Number: |
| LED Light Source Serial Number: |
| |
| or External Light Source Serial Number: |
| Date Purchased: |