

MedRx[®]

www.medrx-usa.com



Tinnometer

Revolutionary Tinnitus Assessment

Test & Track Changes In Tinnitus
Easily with NOAH™ Sessions

MedRx[®]

888-392-1234

To Schedule An Online Demo



Tinnometer

Technical Specs

Standards: Screening Audiometer as per ANSI S3.6-2010, IEC 60645-1:2012, Type 4; Tone Audiometry, Tinnitus assessment

Outputs: Insert Earphones, DD45 Or DD450

Frequency Range: Air: 125 Hz – 8 kHz

Tinnometer Frequency Range: Air: 125 Hz – 16 kHz

Max Output: Air Conduction: 100 dB HL For Mid-Range Frequencies

Attenuation: 1 dB Step Or 5 dB Step, User Selectable

Optional Accessories: DD45 Headphones & Insert Earphones

Compatible with: NOAH™, TIMS® and SycleNet™

Power Requirements: USB-powered

Dimensions: Approx. 5" x 5" x 1" (L x W x H)

Weight: < 1 lb.

Standard Accessories: DD450, Patient Response Switch, Talk-back Microphone, Operator Mic, Monitor Headset, Software & Manuals, Carrying Case

MedRx®

Good Things Come In Small Packages

MedRx, Inc

1200 Starkey Rd. #105

Largo, FL 33771 U.S.A.

888-392-1234 • 727-584-9600

FAX: 727-584-9602

Email: sales@medrx-usa.com

www.medrx-usa.com

MedRx Minimum Computer Specs:

Windows® PC compatible computer, Intel™ i5 Dual Core, 2.0 GHz or better. 4 GB RAM. 20 GB free hard drive space. Available 2.0 USB port. Windows 7, 8 or 10 Professional (32 or 64-bit).



Tinnometer comes standard with the DD450 Headset

MX-TIN-DS-1

