



AVANT AIR+
Screening Audiometer

PC-Based Screening Audiometer

Ideal Audiometer for Traveling.
Use for Community Screenings
Where Only Air Thresholds Are
Needed.



AVANT AIR+

Technical Specs

Standards: Screening Audiometer As Per ANSI S3.6-2018, IEC 60645-1:2012, Type 4; Tone Audiometry

Outputs: DD65v2 Headphones

Frequency Range: Air: 125 Hz – 8 kHz

Max Output: Air Conduction: 100 dB HL For Mid-Range Frequencies

Attenuation: 1 dB Step Or 5 dB Step, User Selectable

Compatible with: NOAH™, TIMS®, Blueprint OMS And Sycle

Power Requirements: USB-Powered

Dimensions: Approx. 12 cm x 12 cm x 3 cm (L x W x H)
Approx. 5" x 5" x 1" (L x W x H)

Weight: < 500 g < 1 lb

Standard Accessories: DD65v2 Headphones, Patient Response Switch, Talkback Microphone, Operator Mic / Monitor Headset, Software & Manuals, Carrying Case

Optional Accessories: DD450 Headphones, DD45 Headphones Or Insert Earphones

MedRx Minimum Computer Specs:

Windows® PC Compatible Computer, Intel™ i5 Dual Core, 2.0 GHz Or Better. 4 GB RAM. 20 GB Free Hard Drive Space. Available 2.0 USB Port. Windows 7, 8 Or 10 Professional (32 Or 64-Bit).

AVANT AIR+ Features

- Air Threshold Testing
- Automatic Air Audiometry Testing
- 125 Hz - 8 kHz
- Small Footprint:
Approx. 12 cm x 12 cm x 3 cm (L x W x H)
- PC-based via USB Connection
- HID device - True Plug and Play
- NOAH™, TIMS®, Blueprint OMS and Sycle Compatible

MedRx®

Good Things Come in Small Packages

MedRx International

MAICO Diagnostics GmbH

Sickingenstr. 70-71

10553 Berlin, Germany

Phone: +49 30 70 71 46 50

Fax: +49 30 70 71 46 99

Email: medrx-sales@maico.biz

www.medrx-diagnostics.com

Distributed by:



AVANT AIR+ comes standard with the DD65v2 Headphones.

MX-AIR-INTDS-1 Rev. 1

