


OTICON | More


Fitting range*



□ OpenBass dome
■ Mold, Bass & Power dome

OSPL90 (peak)
Ear simulator 116 dB SPL
2cc coupler 106 dB SPL


Full-on gain (peak)
Ear simulator 46 dB
2cc coupler 36 dB



■ Power Receiver Mold, Bass & Power dome

OSPL90 (peak)
Ear simulator 132 dB SPL
2cc coupler 124 dB SPL


Full-on gain (peak)
Ear simulator 66 dB
2cc coupler 57 dB



□ OpenBass dome
■ Mold, Bass & Power dome

OSPL90 (peak)
Ear simulator 127 dB SPL
2cc coupler 117 dB SPL

Full-on gain (peak)
Ear simulator 66 dB
2cc coupler 55 dB



■ Power Receiver Mold

OSPL90 (peak)
Ear simulator 135 dB SPL
2cc coupler 127 dB SPL

Full-on gain (peak)
Ear simulator 72 dB
2cc coupler 64 dB

*Fitting range is based on Oticon More 1. Fitting range for Oticon More 2 & Oticon More 3 is limited to 8 kHz. Details available in Technical data sheets.

Easy, discreet miniRITE R



Oticon More miniRITE R is a discreet, rechargeable hearing aid with a lithium-ion battery and an easy to use charger.


Oticon More miniRITE R comes with groundbreaking new features and functionalities that give access to the full perspective of sounds. It is a Made for iPhone® hearing aid which also offers sound streaming direct from selected Android devices.**

Oticon More miniRITE R uses the proven miniFIT receivers and ear pieces and fits up to 105 dB HL.

**Oticon More is compatible with Android's Audio Streaming for Hearing Aids protocol (ASHA) – meaning it supports direct streaming from selected Android devices.

miniFit receivers and Power Receiver Molds

Select between three receivers with different output performance, with lengths 0-5 for non power speakers and 1-5 for power. The 105 receiver requires a custom Power Receiver Mold.



Earpieces

miniFit earpieces include standard domes, Grip Tips, MicroMold, and LiteTip. Custom earpieces are available in acrylic, soft silicone or VarioTherm® material.




IP68

Proven IP68 water and dust resistant hearing aids.



OTICON | More Product comparison



TwinLink
NFMI + 2.4 GHz

oticon
life-changing technology

		More 1	More 2	More 3
Speech Understanding	MoreSound Intelligence™	Level 1	Level 2	Level 3
	- Environment configuration	5 Options	5 Options	3 Options
	- Virtual Outer Ear	3 Configurations	1 Configuration	1 Configuration
	- Spatial Balancer	100%	60%	60%
	- Neural Noise Suppression, Difficult/Easy	10 dB/4 dB	6 dB/2 dB	6 dB/0 dB
	- Sound Enhancer	3 Configurations	2 Configurations	1 Configuration
	MoreSound Amplifier™	•	•	•
	Feedback Prevention	MoreSound Optimizer™ & Feedback shield	MoreSound Optimizer™ & Feedback shield	MoreSound Optimizer™ & Feedback shield
	Spatial Sound™	4 Estimators	2 Estimators	2 Estimators
	Soft Speech Booster	•	•	•
	Frequency lowering	Speech Rescue™	Speech Rescue™	Speech Rescue™
Sound Quality	Clear Dynamics	•	•	
	Better-Ear Priority	•	•	
	Fitting Bandwidth*	10 kHz	8 kHz	8 kHz
	Bass Boost (streaming)	•	•	•
	Processing Channels	64	48	48
Listening Comfort	Transient Noise Management	4 configurations	3 configurations	3 configurations
	Wind Noise Management	•	•	•
Personalization & Optimizing Fitting	Fitting Bands	24	20	18
	Multiple Directionality options	•	•	•
	Adaptation Manager	•	•	•
	Fitting Formulas	VAC+, NAL-NL1/NAL-NL2, DSL 5.0	VAC+, NAL-NL1/NAL-NL2, DSL 5.0	VAC+, NAL-NL1/NAL-NL2, DSL 5.0
Connecting to the world	Stereo streaming (2.4 GHz)	•	•	•
	Oticon ON App & Oticon RemoteCare App	•	•	•
	ConnectClip	•	•	•
	EduMic	•	•	•
	Remote Control 3.0	•	•	•
	TV Adapter 3.0	•	•	•
	Phone Adapter 2.0 (with ConnectClip)	•	•	•
	Tinnitus SoundSupport™	•	•	•

*Bandwidth accessible for gain adjustments during fitting