

PHILIPS

Philips HearLink 9030 custom order form

Today's date: / /
MM DD YYYY

Your information

Ship to information

Account number

Phone number

Company name

Address

City State Zip

Bill to information

Bill to number

Fax orders to (800) 327-5582

Member information

Patient ID Age

PO/insurance/authorization number

Special processing

Loss/damage (affirmation required) Model change

Left serial number

Right serial number

Product selection

Left Right Binaural

SEE PAGE 2 FOR MORE DETAILS			Speaker 75 ¹	Speaker 90 ¹	Speaker 100 ¹	Dirx	NFMI ²	2.4 GHz Wireless ^{2,3}	Telecoil ³ NO 2.4GHz	Program button	VC wheel
Model	Battery	*No size 13 Available	L R	L R	L R	L R	L R	L R	L R	L R	L R
IIC	10		<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	NA	NA	NA	NA	NA	NA	NA
CIC	10		<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	NA	NA	<input type="checkbox"/> <input type="checkbox"/>	NA	NA	<input type="checkbox"/> <input type="checkbox"/>	NA
ITC	312*		<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	S	S	S	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
ITE HS	312*		<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	S	S	S	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>
ITE FS	312*		<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	S	S	S	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>

Product options

Faceplate	Shell color	Canal length (Factory select unless marked)	Vent style ⁴ (See back)	Vent size (Factory select unless marked)
<input checked="" type="checkbox"/> Beige	<input checked="" type="checkbox"/> Beige	<input type="checkbox"/> As marked	<input checked="" type="checkbox"/> Round	<input type="checkbox"/> Largest possible <input type="checkbox"/> 1.6 mm
<input type="checkbox"/> Light brown	<input type="checkbox"/> Light brown	<input type="checkbox"/> Long (before 2nd bend)	<input type="checkbox"/> Collection	<input type="checkbox"/> 3.0 mm <input type="checkbox"/> 1.4 mm
<input type="checkbox"/> Medium brown	<input type="checkbox"/> Medium brown	<input type="checkbox"/> Short (before 1st bend)	<input type="checkbox"/> Oval	<input type="checkbox"/> 2.4 mm <input type="checkbox"/> 1.2 mm
<input type="checkbox"/> Dark brown	<input type="checkbox"/> Dark brown	<input type="checkbox"/> Deep (at 2nd bend)	<input type="checkbox"/> Free (N/A on IIC)	<input type="checkbox"/> 2.0 mm <input type="checkbox"/> Pressure
<input type="checkbox"/> Black	<input type="checkbox"/> Black	<input type="checkbox"/> Medium (at 1st bend)		<input type="checkbox"/> 1.8 mm <input type="checkbox"/> No vent
	<input type="checkbox"/> Red or blue			
	<input type="checkbox"/> Clear/ translucent			

Audiometric information (required)

Hz	250	500	1000	2000	3000	4000	6000
AC right							
AC left							

Connectivity options*

TV Adapter Remote Control AudioClip
*Requires 2.4GHz Wireless

Special instructions:

Please call if substitutions are required.

Internal use only: do not write

Other options

Retention Canal lock Soft coat Metal loop

Removal Removal cord (Std. on CICs, IICs) Removal notch
 Large ball removal cord

Tactile Raised program button Raised VC wheel

Other Color dots

Custom products reference guide

Venting

Round vent	Oval vent	Free vent/largest possible	Collection vent

Vent type is selected at the factory, unless otherwise noted in the special instructions.

Moisture protection

T-Cap mic cover	O-Cap mic cover	ProWax receiver cover

Other options

Retention	Removal	Tactile

Options available space permitting, and may not be available on all models.

1) Indicates fitting range. Refer to technical information below. *Factory select unless marked.

75 receiver: OSPL90 PK 108, PK Gain 41
90 receiver: OSPL90 PK 120, PK Gain 55
100 receiver: OSPL90 PK 125, PK Gain 63

*2cc coupler minimum values in dB SPL, dB

2) Near-field magnetic induction (NFMI) enables binaural communication between right/left instruments.

3) Hearing aid(s) cannot accommodate both a telecoil and 2.4 GHz wireless. Please choose only one option.

4) Free vent not available in IIC.

